

• The Monoshox NG Plus M technical features

Frame	Single telescopic						Double telescopic			Extend 6	
	Monobloc		Monobloc2 Comfort		Monobloc2 Comfort Mixed		Monobloc	Monobloc2 Comfort			
Width	4.5m		4.5m		4.5m		4.5m	4.5m	4.5m	7m 4.5m	
Transporting width	3.5m		3.5m		3.5m		3m	3m	3m*	3m	
Number of elements	6	7	8	6	7	8	7	6	6	7	6
Row spacing (in cm)	75/80	85/90	45/49	75/80	50/55/60	49	75 (2x on 80) (3 rows) 50/2 (49/50) (7 rows)	75/80	75/80	55/60 65/70	45/50 55/60 65/70 75/80
Turbine	Power take-off drive - standard 540 rpm, optional 470 or 1.000 rpm Optional hydraulic drive, optional universal joint free-wheel										
Types	2 x (6.5x80x15)		2 x (20x12)		2 x (20 x 12)		2 x (20x12)		2 x (20x12)		2 x (20x12)
Drive	Mechanical	Distance gearbox	Standard	▷ 1	-	-	-	▷ 1	-	-	-
		Lateral	-	● 1	● 1	-	● 1	● 1	● 1	● 1	● 1
	EasyGear	● 1	-	-	-	● 1	-	-	-	-	-
Electric	▷	■	▷	▷	■	▷	▷	▷	▷	▷	
Hydraulic markers	●		●		●		●		●		●
FrontBar	Standard	▷ 2 x 270L	-	-	-	-	▷ 2 x 270L	-	-	-	-
	"High-capacity"	▷ 900L	▷ 1 x 680L or 1 x 1010L	1 x 680L	▷ 1 x 1010L	▷ 900L	1 x 680L	▷ 1 x 1010L	1 x 680L	▷ 1010L	1 x 680L
	Front Standard	▷	+	▷	▷	▷	▷	▷	▷	▷	▷
	Front DUD	-	-	-	-	-	-	-	-	-	-
Microson	Insecticide	▷	▷	▷	▷	▷	▷	▷	▷	▷	
	Herbicide	▷	▷	▷	▷	▷	▷	▷	▷	▷	
Hectare counter	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
Sowing controllers	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
Row breaks	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
Lighting kit	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
Weight of seed planter alone	1100kg	1423kg	1550kg	1500kg	1625kg	1750kg	1625kg	1500kg	1550kg	1675kg	1700kg

● Standard ▷ Optional + Inexpensive * According to weight ■ Consult us

Extend 6/7	Multiside			Folding																
	7	8	9	Double bar			TTC Floating		TTC Right		TTC Comfort					TTC Comfort Mixed		CR1		
1.1m 4.5m	2.55m	3m	3m	6m	7m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	9m	
3.1m	2.55m	3m	3m	3m	3m	3.5m	3m	3m	3m	3m*					3m*	3m*	3m*	3.5m*		
7	7	8	9	8	9	11	12	8	8	8	9	11	12	16	11	12	12	12	11	
75/80 85/90 45/50 55/60 65/70	■			75/80	60	60	45/50	75/80	75/80	75/80	75/80	55/60/65	55	45/50	37.5	75 or 80 (8 rows)	75 or 80 (7 rows)	75 or 80 (5 or 10 rows)	70/75/80	40
Power take-off drive - standard 540 rpm, optional 470 or 1.000 rpm Optional hydraulic drive, optional universal joint free-wheel																				
2 x (20x12)	2 x (13 x 10.5) 2 x (20 x 12)		4 x (6.5x80x15)				4 x (20x12) 2 x (20x12)				4 x (26x12)				4 x (26x12)		4 x (6.5x80x15)			
-	-	-	▷ 3	▷ 3	-	▷ 3	-	▷ 3	-	▷ 3	-	▷ 3	-	▷ 3	-	▷ 3	-	▷ 3	-	
● 1	-	-	-	-	-	-	-	● 1	-	-	-	-	-	-	-	-	-	-	-	
-	● 1	-	-	-	-	-	-	● 1	-	-	-	-	-	-	-	-	-	-	-	
▷	●	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
-	-	-	-	-	-	-	-	▷ 1500L	▷ 1500L	▷ 1500L	▷ 1500L	-	-	-	-	-	-	-	-	
▷	■	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	▷	
1850kg	1917kg	2081kg	2337kg	2258kg	2358kg	2600kg	2558kg	2900kg hydraulic	2850kg hydraulic	2708kg	2800kg	3000kg	3100kg	3500kg	3050kg	3150kg	3500kg	3500kg	3500kg	

For more details, contact us via type of frame element.