

• The Monoshox NX M technical features

● Standard ○ Option - : Inoperable * : According to model (1) : Inter-row spacing 80cm

7" TOP Full-type frames							
Rigid			Folding				
3,2m	5,1m	6,7m	4,5m	4,5m	6m	6,8m	9,2m
3,2m	5,1m	6,7m	3m	3,4m	3m	3,4m	5m
4	6	8	6	6	8	8	12
70	75	76,2	80	70-75	80 ¹⁾	70-75	80
Power take-off drive - standard 540 rpm, optional 450 or 1,000 rpm Wide angle universal joint, optional hydraulic drive, optional universal joint freewheel							
2 x 17,5x20	4 x 17,5x20	4 x 17,5x20	2 x 265/70R19,5	2 x 265/70R19,5	2 x 265/70R19,5	2 x 265/70R19,5	6 x 17,5x20
-	1	1	-	-	-	-	1
-	-	-	1	1	1	1	-
○	○	○	○	○	○	○	○
●	●	●	●	●	●	●	●
-	-	-	-	-	-	-	4 x 220L
2 x 400L	2 x 700L	2 x 1000L	2 x 1000L	2 x 1000L	1 x 1500L (or 1500L) ²⁾	1 x 1500L (or 1500L) ²⁾	•
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○
○	○	○	●	●	●	●	○
1600kg (1900kg)	2450kg (2850kg)	3600kg (3600kg)	3600kg (3600kg)	3500kg (3500kg)	3100kg (3500kg)	3100kg (3500kg)	4250kg (3500kg)

For other models, configurations or other needs:

MONOSEN